

HCPP Block Copolymer Pipe Grade
YUHWA POLYPRO BP2000

Description

- Application : Pipe
- Features : High Stiffness and Impact Strength Especially at low temperature, Creep Resistance, Chemical Resistance, Color:Natural,Gray,Yellow
- Uses : Water Supply and Drain Pipes

Properties

Item	Value	Unit	Test Method
Melt Index	0.3	g/10min.	ASTM D1238
Density	0.91	g/cm ³	ASTM D1505
Tensile Strength at Yield	240	kg _f /cm ²	ASTM D638
Elongation at Break	>600	%	ASTM D638
Flexural Modulus	13,000	kg _f /cm ²	ASTM D790
Hardness (Rockwell)	80	R Scale	ASTM D785
Impact Strength (Izod with Notch)	NB	kg _f cm/cm	ASTM D256
Vicat Softening Point	153	°C	ASTM D1525
Oxidation Induction Time at 200°C	>30	min	ASTM D3895
Heat Deflection Temperature	100	°C	ASTM D648

- Above data are intended to serve as guides only, and are not sales specification limits.
- YUHWA POLYPRO BP2000 complies with FDA regulations.

Contact Info

International Trade

TEL: 82-2-3706-0840-0849 FAX: 82-2-3706-0864-0865 e-mail: trade@kpicc.com

Technical Service

TEL: 82-80-010-1515, 82-2-2122-1531-1534 FAX: 82-2-2122-1519 e-mail: H15105@kpic.co.kr